

# TYPE N CONTROLLERS

# LEES TECH

www.leestech.com

Operation is Maintained UP (“Latching”)

STOP

Push to Run DOWN (“DEAD MAN” or “INCHING”)

## FEATURES

- 400V Three Phase/240V Coil
- Digital Counter
- Housed in an IP65 plastic enclosure and comprising of UP/DOWN contactors, overload relay and terminals for supply/motor/limit switch
- Available in both **Single** and **3 Phase**
- Simple operation using UP/STOP/DOWN pushbuttons
- Press and release UP pushbutton to open. Door will open until it reaches the UP limit or STOP button is pressed
- Press and hold DOWN pushbutton to close. Operation will stop when the pushbutton is released or when door reaches the pre-set limit
- To stop door during open cycle press STOP pushbutton. Press UP or DOWN pushbutton to resume operation
- Overload



## SINGLE PHASE

Suitable for 230V 50Hz Single Phase Motor

MODEL	MAX RATING	WIRING DIAGRAM
DC-1N-C	0.75kW	

## THREE PHASE

Suitable for 400V 50Hz Three Phase Motor

MODEL	MAX RATING	WIRING DIAGRAM
DC-3N-C	2.2kW	1162

LEES TECHNOLOGY NZ LTD

3E Tait Place, Albany, Auckland 0632, New Zealand  
Tel: 09 447 1093 | Fax: 09 447 1094 | Mobile: 021 737 962  
info@leestech.com

Digi-Code

LEES TECHNOLOGY AUSTRALIA

14 Christine Ave, Gold Coast, QLD 4226, Australia  
Tel: 07 5520 7178 | Mobile: 0420 904 780  
riki@leestech.com

LEES TECH  
www.leestech.com

Motorpol